

Victor



SPECIFICATION


- ▼ Voltage – 650/1300 Volt
- ▼ Current – 350 Amp
- ▼ 3 Mains contact pins
- ▼ 1 Pilot contact pin
- ▼ Weight – 11kg.
- ▼ Conductor CSA up to 120mm²
- ▼ Interface flange to BS 5620

FEATURES & BENEFITS

- ▼ Contact pins can be grubscrewed or crimped.
- ▼ Earth screened insulator.
- ▼ Electrical interlock through pilot circuit.
- ▼ Simple serviceable design.
- ▼ To facilitate the connection of trailing cables fitted with Type A40PR, 40PR, and 23PR restrained plugs to high powered mining machinery such as continuous miners, roadheaders, and other large capacity apparatus. Suitable for deep mine and opencast environments.

STANDARDS & CERTIFICATION

EN IEC 60079-0: 2018, EN 60079-1: 2014
ATEX Certificate No. Baseefa02ATEX0099U

 I M2 Ex db I Mb

UKEX Certificate No. BAS21UKEX0319U


 I M2 Ex db I Mb

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS004 REV 1 01/24

Type A40SR 650/1300V 350A Restrained Socket