



## SPECIFICATION

- ▼ Provision of 3 power, 1 pilot and 2 auxiliary contacts with scraping earth.
- ▼ Full integral earth screening through insulator.
- ▼ Current rating – 500 Amps.
- ▼ Voltage – 3300 Volts.
- ▼ Weight – 8.7 kgs.


## FEATURES & BENEFITS

- ▼ Compact size and weight.
- ▼ Robust construction.
- ▼ Rotary switch operation.
- ▼ To Facilitate the testing of pilot circuits in electrical equipment designed to BS3101.
- ▼ Suitable for deep mine and opencast environments.


## STANDARDS & CERTIFICATION

EN IEC 60079-0: 2018 & EN IEC 60079-1: 2014

Certificate No. Baseefa 09ATEX0121U

 I M2 Ex db I Mb

UKEx Certificate No. BAS22UKEX0031U

 I M2 Ex db I Mb

IECEX Certificate No. BAS 09.0048U


Ex db I Mb

For more information on possible variants please contact Victor Sales:  
Tel: 0191 280 8000, Email: sales@victor.co.uk



**Victor**

**VICTOR PRODUCTS LIMITED**

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom  
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk  
A Federal  Signal Company

LEAFLET NO. DS009 REV 0 02/24