


SPECIFICATION

- ▼ Provision of 3 power, 1 pilot contact with scraping earth.
- ▼ Full integral earth screening through insulator.
- ▼ Current rating – 350 Amps.
- ▼ Voltage – 650/1300 Volts.
- ▼ Weight – 24 kgs.

STANDARDS & CERTIFICATION

EN IEC 60079-0: 2018 & EN 60079-1: 2014

Certificate No. Baseefa 02ATEX0100

 I M2 Ex db I Mb

UKEx Certificate No. BAS21UKEX0320

 I M2 Ex db I Mb

FEATURES & BENEFITS


- ▼ Minimal spares stockholding.
- ▼ Compact size and weight.
- ▼ Simple serviceable design.
- ▼ To Facilitate the connection of 2 trailing cables, fitted with suitable mating Type A40PR plug.
- ▼ Suitable for deep mine and opencast environments.
- ▼ Certified for Group 1 hazardous areas where electrical interlock by means of the pilot circuit is an essential system requirement.
- ▼ Ideally suited to joining short runs of cable which are prone to mechanical damage, in advancing tunnels, roadways and mid-face situations.

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS014 REV 0 02/24