



SECTION X-X

NOTE: INSULATOR IS SHOWN ASSEMBLED IN 1100 VOLT MODE. FOR 3300 VOLT MODE, THE INSULATOR IS ROTATED THROUGH 180°.

DRAWING No.	ISSUE No.
CP302	
CERTIFICATE RELATED DRAWING	
NO MODIFICATIONS PERMITTED WITHOUT THE APPROVAL OF THE TECHNICAL MANAGER	
DO NOT SCALE	
DIMENSIONS IN MILLIMETRES (mm)	
MAXIMUM MACHINED SURFACE	
TEXTURE $\mu m Ra 3.2$	
MACHINE WHERE MARKED THUS <input checked="" type="checkbox"/>	
ANGULAR TOLERANCES $\pm 1/2^\circ$	
DIMENSIONAL TOLERANCES UNLESS OTHERWISE STATED	
UPTO 6	± 0.1
OVER 6 UPTO 30	± 0.2
OVER 30 UPTO 100	± 0.3
OVER 100 UPTO 300	± 0.5
OVER 300	± 0.8
TEST No.	PROCESS No.
200	---
DRAWN	AER
DATE	3/8/10
CHECKED	3/8/10 AER
APPROVED	3/8/10 AER
SCALE	1:1

DCR	DRN	3/8/10	AER
CHK	3/8/10	AER	APP
		3/8/10	AER

DRAWING INTRODUCED.

RESTRAINED PLUG COUPLER - TYPE 3RPCA
1100/3300 VOLTS 500 AMPS.

Victor
Victor Products Limited
Unit 3A, Tyne Dock East Side,
Port of Tyne, South Shields,
Tyne and Wear, NE33 5SQ,
United Kingdom.

DRAWING No.	ISSUE No.
SHEET 1 OF 1	
CP302	0