

1 UK-TYPE EXAMINATION CERTIFICATE

2 Equipment or Protective System Intended for use in Potentially Explosive Atmospheres UKSI 2016:1107 (as amended) – Schedule 3A, Part 1

- 3 UK-Type Examination BAS21UKEX0320 Certificate Number:
- 4 Product: Type A40SCR Restrained Plug Coupler
- 5 Manufacturer: VICTOR PRODUCTS LIMITED
- 6 Address: New York Way, New York Industrial Park, Newcastle-upon-Tyne, NE27 0QF
- 7 This product and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.
- 8 SGS Baseefa, Approved Body number 1180, in accordance with Regulation 43 of the Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016, UKSI 2016:1107 (as amended), certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Schedule 1 of the Regulations.

The examination and test results are recorded in confidential Report No. 21(C)0261

9 Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN IEC 60079-0:2018 EN 60079-1: 2014

except in respect of those requirements listed at item 18 of the Schedule.

- **10** If the sign "X" is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.
- 11 This UK-TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified product. Further requirements of the Regulations apply to the manufacturing process and supply of this product. These are not covered by this certificate.
- 12 The marking of the product shall include the following:

⟨ IM2 Ex db IMb

SGS Baseefa Customer Reference No. 1186

Project File No. 21/0261

This document is issued by the Company subject to its General Conditions for Certification Services accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. It does not necessarily indicate that the equipment may be used in particular industries or circumstances. The Company's sole responsibility is to its Client and this document does not except in full, schedule included, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.





16. Qui

R S SINCLAIR TECHNICAL MANAGER On behalf of SGS Baseefa Limited



Schedule

13 14

Certificate Number BAS21UKEX0320

15 Description of Product

Type A40SCR Restrained Plug Coupler, rated at up to 350A, 650/1300V. The coupler comprises a brass and gunmetal enclosure, incorporating an insulator assembly with three main contact pins and a pilot circuit contact pin.

A location pin in the coupler body enables the contact pin assembly to be set in the 650v or 1300V mode.

The coupler has a mounting at each end for restrained plugs or restrained test plugs, suitably certified for Group I use.

The coupler body is provided with holes for a padlock.

16 Report Number

SGS Baseefa Certification Report 21(C)0261

17 Specific Conditions of Use

None

18 Essential Health and Safety Requirements

In addition to the Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9, the following are considered relevant to this product, and conformity is demonstrated in the report:

Clause	Subject		
1.2.7	LVD Type Requirements		
1.4.1	External effects		
1.4.2	Aggressive substances, etc.		

19 Drawings and Documents

Number	Sheet	Issue	Date	Description
CA185	1 of 2	2	15/01/20	Restrained Plug Coupler – Type A40SCR and Variants 350 Amps 650/1300 Volts.
CA185	2 of 2	2	15/01/20	Restrained Plug Coupler – Type A40SCR and Variants 350 Amps 650/1300 Volts.

These drawings are common to Baseefa02ATEX0100, BAS21UKEX0320 and held with the former.