



SPECIFICATION

- ▼ Voltage – 650/1300 Volt
- ▼ Current – 350 Amp
- ▼ 3 Mains contact tubes.
- ▼ 1 Pilot contact tube
- ▼ Weight – 10kg.
- ▼ Conductor CSA up to 120mm²
- ▼ Cable diameter range 26-73mm

FEATURES & BENEFITS

- ▼ Contact tubes can be grubscrewed or crimped.
- ▼ Earth termination in earth screen clamp.
- ▼ Earth screened insulator.
- ▼ Electrical interlock through pilot circuit.
- ▼ For the termination and connection of unarmoured flexible trailing cables for use in deep mining and opencast environments.
- ▼ Simple serviceable design.
- ▼ For use with Type A40SR, 40SR, and 23SR, range of Restrained Sockets, and Type A40SCR, 40SCR, and 23SCR range of Restrained Plug Couplers.

STANDARDS & CERTIFICATION

EN IEC 60079-0: 2018, EN 60079-1: 2014
ATEX Certificate No. Baseefa02ATEX0098U

 I M2 Ex db I Mb

UKEX Certificate No. BAS21UKEX0318U

 I M2 Ex db I Mb

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS003 REV 1 01/24