

Victor



SPECIFICATION

- ▼ Voltage – 3000 Volt
- ▼ Current – 500 Amp
- ▼ 3 Mains contact pins
- ▼ 1 Pilot contact pin
- ▼ 2 Auxiliary pins
- ▼ Weight – 10kg.
- ▼ Conductor CSA up to 185mm²
- ▼ Interface flange to BS 5620


FEATURES & BENEFITS

- ▼ Contact pins can be grubscrewed or crimped.
- ▼ Earth screened insulator.
- ▼ Electrical interlock through pilot circuit.
- ▼ Simple serviceable design.
- ▼ To facilitate the connection of trailing cables fitted with Type A43PB Bolted Plug. Suitable for deep mine and opencast environments.

STANDARDS & CERTIFICATION

EN IEC 60079-0, EN 60079-1

ATEX Certificate No. Baseefa09ATEX0121U

 I M2 Ex db I Mb

UKEX Certificate No. BAS22UKEX0031U

 I M2 Ex db I Mb

IECEx Certificate No. IECEx BAS 09.0048U

Ex db I Mb

For more information on possible variants please contact Victor Sales:

Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk

A Federal  Signal Company

LEAFLET NO. DS006 REV 0 01/24

Type A43SB 3300V 500A Bolted Socket