




SPECIFICATION

- ▼ Provision of 3 power, 1 pilot and 2 auxiliary contacts with scraping earth.
- ▼ Current rating – 500 Amps.
- ▼ Voltage – 3300 Volts.
- ▼ Weight – 13 kgs.


STANDARDS & CERTIFICATION

EN IEC 60079-0: 2018 & EN IEC 60079-1: 2014

Certificate No. Baseefa 09ATEX0122X

 I M2 Ex db I Mb

UKEx Certificate No. BAS22UKEX0030X

 I M2 Ex db I Mb

IECEX Certificate No. BAS 09.0049X

Ex db I Mb

FEATURES & BENEFITS


- ▼ Minimal spares stockholding.
- ▼ Compact size and weight.
- ▼ Simple serviceable design.
- ▼ To Facilitate the connection of 2 trailing cables, fitted with suitable mating Type A43PB plugs.
- ▼ Suitable for deep mine and opencast environments.
- ▼ Can be used in systems with or without electrical interlock by means of the pilot circuit.
- ▼ Ideally suited to joining short runs of cable which are prone to mechanical damage.

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS008 REV 0 01/24