




SPECIFICATION

- ▼ Provision of 3 power, 1 pilot and 2 auxiliary contacts with scraping earth facility.
- ▼ Full integral earth screening through insulator.
- ▼ Current rating – 500 Amps.
- ▼ Voltage – 1100 / 3300 Volts.
- ▼ Weight – 13.5 kgs.

STANDARDS & CERTIFICATION

EN 50014: 1997 and EN 50018: 2000.
ATEX Certificate No. BASEEFA02ATEX0133.

 I M2 EEx d I

FEATURES & BENEFITS


- ▼ Minimal spares stockholding.
- ▼ Compact size and weight.
- ▼ Simple serviceable design.
- ▼ Common parts used in restrained and bolted versions.
- ▼ Two voltage modes – 1100 and 3300V.
- ▼ Provision for use of padlock at both ends.
- ▼ To Facilitate the connection of 2 trailing cables, fitted with suitable mating Type 30PA plugs.
- ▼ Suitable for deep mine and opencast environments.
- ▼ Certified for Group 1 hazardous areas where electrical interlock by means of the pilot circuit is an essential system requirement.
- ▼ Used to extend cable runs in advancing tunnels, roadways and mid-face situations.

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS010 REV 0 02/24