



SPECIFICATION

- ▼ Provision of 3 power, 1 pilot and 2 auxiliary contacts with scraping earth facility.
- ▼ Full integral earth screening through insulator.
- ▼ Voltage – 1100/3300 Volt
- ▼ Current – 500 Amp
- ▼ Weight – 10.3kg.
- ▼ Conductor CSA up to 120mm²

STANDARDS & CERTIFICATION

EN 50014: 1997 and EN 50018: 2000
Certificate No. Baseefa02ATEX0132U

 I M2 EEx d I

FEATURES & BENEFITS


- ▼ Minimal spares stockholding.
- ▼ Compact size and weight.
- ▼ Easy cable make-off.
- ▼ Common parts used on restrained and bolted version.
- ▼ Simple serviceable design.
- ▼ Simple serviceable design.
- ▼ For the termination and connection of flexible trailing cables for deep mines and opencast environments.
- ▼ Certified for Group 1 hazardous areas where a need for mechanical interlock exists.
- ▼ Can be used in systems with or without interlock by means of a pilot circuit.
- ▼ For use with Type 530SA restrained socket and plug couplers.
- ▼ Alternative P.W.A/cable clamp for pliable wire armoured cables.

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS011 REV 1 02/24