



## SPECIFICATION

- ▼ Provision of 3 power, 1 pilot and 2 auxiliary contacts with scraping earth facility.
- ▼ Full integral earth screening through insulator.
- ▼ Voltage – 1100/3300V.
- ▼ Current – 500 Amps.
- ▼ Weight – 11.6Kgs.

## FEATURES & BENEFITS

- ▼ Minimal spares stockholding.
- ▼ Two Voltage modes 1100 & 3300V.
- ▼ Use with padlock facility.
- ▼ Used to facilitate the connection of trailing cables, fitted with a suitable type 30 plug.
- ▼ Suitable for deep mine and opencast environments.
- ▼ Socket mounting flange designed to BS 5620.

## STANDARDS & CERTIFICATION

EN 50014: 1997, EN 50018: 2000  
ATEX Certificate No. Baseefa02ATEX0131U


 I M2 EEx d I

For more information on possible variants please contact Victor Sales:  
Tel: 0191 280 8000, Email: sales@victor.co.uk



**Victor**

**VICTOR PRODUCTS LIMITED**

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom  
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk  
A Federal  Signal Company

LEAFLET NO. DS013 REV 0 02/24