



SPECIFICATION

- ▼ Provision of 3 contact tubes (crimped type) as standard.
- ▼ Suitable for stranded conductors, Copper or Aluminium, up to 185mm².
- ▼ Current rating – 500 Amps.
- ▼ Voltage – 3300 Volts.
- ▼ Weight – 10 kgs (unfilled) - 14kgs (filled).

STANDARDS & CERTIFICATION

EN 50014: 1997 + Amds 1&2
and EN 50018: 2000
ATEX Certificate No. MECS 02ATEX5087U
ATEX Certificate No. MECS 02ATEX5088
(coupler pair).
 I M2 EExd I

FEATURES & BENEFITS

- ▼ Compact size and weight.
- ▼ Heavy duty metal body.
- ▼ Fast make-off.
- ▼ Suitable for Unarmoured and Pliable wire armour (PWA) cables.
- ▼ Suitable for Group 1 hazardous areas.
- ▼ Suitable for the termination and connection of mains cables for deep mine, opencast and industrial environments.
- ▼ Removable pins enable connection with a mating half coupler, adaptor or other suitable equipment.
- ▼ Coupler must be solid filled after make-off – See fitting instructions.
- ▼ For armoured cable please see MK2 design.
- ▼ Up to 7 Pilot / Auxiliary available with unarmoured cable

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS015 REV 0 03/24