

Victor



SPECIFICATION

- ▼ Provision of 3 power and 1 pilot contact.
- ▼ Voltage – 650/1300 Volt
- ▼ Current – 250 Amp
- ▼ Weight – 6kg.
- ▼ Conductor CSA up to 70mm²
- ▼ Cable diameter range 25-60mm

STANDARDS & CERTIFICATION

EN 50014: 1997 + Amds 1 & 2
and EN 50018: 2000

ATEX Certificate No. MECS02ATEX5101U (PR)

ATEX Certificate No. MECS02ATEX5098U (PB)

 I M2 EEx d I

FEATURES & BENEFITS


- ▼ Common parts used in PR and PB version.
- ▼ Scraping earth facility.
- ▼ Alternative P.W.A / Screen clamp for P.W.A cables (A41PR/A & A41PB/A)
- ▼ For the termination and connection of unarmoured and P.W.A flexible trailing cables, for use in deep mining and opencast environments.
- ▼ Simple serviceable design.
- ▼ For use with Type A41SR and Type A41SB sockets.

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS018 REV 0 03/24

Type A41PR / A41PB 650/1300V 250A Restrained & Bolted Plug