



SPECIFICATION

- ▼ MSHA Approved.
- ▼ Voltage ranges – 12V AC/DC or 24V AC/DC
- ▼ Cable Entries:
2 x 1 1/8" - 12 UNF
- ▼ Clear or Frosted Glass available.
- ▼ Available in Brass.
- ▼ Spot Lens beam option
- ▼ Dimensions 153mm Long x 128mm high*
- ▼ Mounting bracket 160mm wide*

*Detailed dimensions or .STP file available on request.

FEATURES & BENEFITS

- ▼ Low Power Consumption – 0.5A @ 24V
1.0A @ 12V.
- ▼ Low Maintenance.
- ▼ Long LED Lamp Life > 100,000 hours
(temperature dependant)
- ▼ White 'Headlight' and Red 'Taillight'
incorporated in one unit.
- ▼ High Resistance to Vibration & Shock.
- ▼ Greater light output than 70W halogen
equivalent.
- ▼ Provision for internal and external earth.
- ▼ Simple installation with two mounting points.
- ▼ Can be mounted in any orientation.

STANDARDS & CERTIFICATION

Certified as complying with the applicable
requirements of 30CFR Part 18.

Certification Number 18-XPA100016-0.

Commonwealth of Pennsylvania Approval

No. BFE 137-10

Ambient Temperature range: -20°C To +45°C

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk

